



AIAA-81-1164

**New Contact and Gap
Conductance**

**Correlations for Conforming Rough
Surfaces**

M. M. Yovanovich, University of
Waterloo, Ontario, Canada

**AIAA 16th Thermophysics
Conference**

June 23-25/Palo Alto, California

NEW CONTACT AND GAP CONDUCTANCE CORRELATIONS
FOR CONFORMING ROUGH SURFACES

M. M. Yovanovich*

Thermal Engineering Group
Department of Mechanical Engineering
University of Waterloo
Waterloo, Ontario N2L 3G1

Abstract

The theoretical relationships for determining contact, gap and joint conductances are developed for conforming rough surfaces for first loading. The dimensionless conductances are functions of the relative contact pressure, surface parameters, conductivity ratio and a fluid parameter which depends upon several gas and surface characteristics. The proposed conductance correlations are supported quantitatively by some previous experimental results.

Nomenclature

- A_a, A_r = apparent and real contact areas
 a, a_i = mean and distributed contact spot radius
 b, b_i = mean and distributed flux tube radius
 C = $\frac{gh}{k_s}$ dimensionless contact conductance
 C_c, C_g, C_j = contact, gap and joint dimensionless conductances
 H = hardness
 h_c, h_g, h_j = contact, gap and joint conductances
 K = k_{g0}/k_s conductivity ratio
 k_1, k_2 = conductivity of the contacting solids
 k_g, k_{g0}, k_s = gap, gas and harmonic mean conductivities
 M = $\alpha \delta \lambda$ gas parameter
 m = mean absolute surface slope
 n = contact spot density
 P, P_g, P_{g0} = relative contact pressure, gas pressure and reference gas pressure
 Pr = $\mu C_p / k_g$ Prandtl number
 Q = heat flow rate
 R_c, R_{ci} = contact and contact spot constriction resistance
 T, T_0 = gap and reference temperature
 ΔT_c = contact temperature drop
 x = $Y/\sqrt{2\sigma}$ dimensionless parameter
 Y, Y_e = separation and effective separation between the surfaces

Greek Symbols

- $\alpha, \alpha_1, \alpha_2$ = accommodation parameter and accommodation coefficients for solids 1 and 2
 β = $(2Y/Y+1)/Pr$ gas parameter
 γ = C_p/C_v specific heat ratio
 λ, λ_0 = molecular mean free path
 $\sigma, \sigma_1, \sigma_2$ = effective surface roughness and surface roughnesses of solids 1 and 2
 ψ_c, ψ_{ci} = mean and contact spot constriction parameters.

Introduction

The problem of predicting and measuring contact, gap and joint thermal conductances has received considerable attention during the past two decades because of the importance of the topic in many heat transfer systems. Comprehensive surveys of literature on this subject can be found in several references [1-8]. Significant progress has been made in our understanding and ability to predict thermal contact conductance. (9,10,11,14,15,18,19,20,22) The study of thermal contact conductance in a vacuum is fundamental to our understanding of thermal gap conductance when interstitial fluids are present. The present state of knowledge has reached a point where simple, explicit correlations can be developed for the contact, gap and joint conductances.

The purpose of this paper is to establish correlations for conforming rough surfaces when interstitial fluids such as greases and gases are present in the gap. The proposed correlations will be compared with existing empirical data to demonstrate quantitatively the validity of the assumptions used to develop the models.

Thermal Conductance Correlations

Geometric, Physical and Thermal Assumptions

The contact and gap conductance correlations developed here are based upon the following assumptions:

- (1) The surfaces are microscopically rough and macroscopically conform-

*Professor, Associate Fellow AIAA

- ing.
- (2) The asperity heights are gaussian and the asperities are randomly distributed over the apparent contact area.
 - (3) The contacting asperities deform plastically during the first loading.
 - (4) The plastic deformation occurs in the softer solid and the flow pressure is constant and approximately equal to three times the elastic limit under tensile stress.
 - (5) During the plastic deformation of the highest peaks, the substrate and the bulk of the solids undergo elastic deformation.
 - (6) As a result of the deformation, there are N circular contact spots within the apparent area A_a .
 - (7) The contact spot radii a_i are distributed.
 - (8) An equivalent circular flux tube of radius b_i is associated with each contact spot.
 - (9) The contact spots are isothermal.
 - (10) The total heat flow rate through each flux tube can be separated into two independent heat flow rates: contact spot and gap flow rates.
 - (11) The effective gap thickness is dependent upon the surface roughness and the relative contact pressure.
 - (12) Noncontinuum gas effects must be taken into account.
 - (13) The surfaces are clean free of oxides, films, etc.
 - (14) Radiative heat transfer is negligible.

Contact Conductance Correlation

The total constriction resistance of the i th contact spot is

$$R_{ci} = \frac{\psi_{ci1}}{4k_1a_i} + \frac{\psi_{ci2}}{4k_2a_i} \quad (1)$$

where ψ_{ci1} and ψ_{ci2} are the thermal constriction (or spreading) parameters which depend upon the relative size of the contact spot. Because of geometric and thermal symmetry about the contact plane we can put

$$\psi_{ci1} = \psi_{ci2} = \psi_{ci} = \left(1 - \frac{a_i}{b_i}\right)^{1.5} \quad (2)$$

provided $0 < a_i/b_i \leq 0.3$.

If we let $k_s = 2k_1k_2/(k_1 + k_2)$, the harmonic mean thermal conductivity, then Eq. (1) can be written as

$$R_{ci} = \psi_{ci}/2k_s a_i \quad (3)$$

The total contact resistance of N contact spots thermally connected in parallel is therefore,

$$\frac{1}{R_c} = \sum_{i=1}^N \frac{1}{R_{ci}} = 2k_s \sum_{i=1}^N \frac{a_i}{\psi_{ci}} \quad (4)$$

The contact conductance can be derived by means of the following definition:

$$Q_c = h_c A_a \Delta T_c = \Delta T_c / R_c \quad (5)$$

Therefore,

$$h_c = \frac{2k_s}{A_a} \sum_{i=1}^N \frac{a_i}{\psi_{ci}} \quad (6)$$

Noting that $a_i/b_i \leq 0.3$ and $0.85 \leq \psi_{ci} < 1$, the specific constriction parameter ψ_{ci} appropriate to each contact spot can be replaced by the mean value of the constriction parameter ψ_c based upon the total set of contact spots.

Therefore we have

$$\psi_{ci} = \psi_c = (1 - \epsilon)^{1.5} \quad (7)$$

where $a/b = \epsilon = \sqrt{A_r/A_a}$. The mean constriction parameter depends upon a and b , the contact spot and associated flux tube radii respectively determined by the total real and apparent areas.

A detailed geometric analysis of interacting conforming rough surfaces (14,19,20) yields the following important geometric results:

i) Contact conductance parameter

$$\sum_{i=1}^N \frac{a_i}{A_a} = \frac{1}{4\sqrt{2\pi}} \frac{m}{\sigma} \exp(-x^2) \quad (8)$$

ii) Relative real contact area

$$\epsilon^2 = \frac{A_r}{A_a} = \frac{1}{2} \operatorname{erfc}(x) \quad (9)$$

iii) Contact spot density

$$n = \frac{1}{16} \left(\frac{m}{\sigma}\right)^2 \frac{\exp(-x^2)}{\operatorname{erfc}(x)} \quad (10)$$

iv) Mean contact spot radius

$$a = \sqrt{\frac{8}{\pi}} \frac{\sigma}{m} \exp(x^2) \operatorname{erfc}(x) \quad (11)$$

where $x = Y/\sqrt{2}\sigma$ and Y/σ is called the relative mean plane separation. The surface parameters σ and m are the effective rms surface roughness and the effective absolute surface slope respectively. They are determined as follows:

$$\sigma^2 = \sigma_1^2 + \sigma_2^2 \quad (12)$$

and

$$m^2 = m_1^2 + m_2^2 \quad (13)$$

Assuming plastic deformation of the contacting asperities during the first loading leads to a relationship between the relative real contact area and the relative contact pressure. A force balance on the real and apparent contact areas gives

$$\frac{P}{H} = \frac{A_r}{A_a} = \epsilon^2 = \frac{1}{2} \operatorname{erfc}(x) \quad (14)$$

This relationship between ϵ and x allows one to compute the other surface parameters. After substitution of the contact conductance parameter, Eq. (8), into the contact conductance expression, Eq. (6), we obtain after multiplying by σ/k_s , the non-dimensional contact conductance,

$$\frac{oh_c}{k_s} = \frac{m}{2\sqrt{2\pi}} \frac{\exp(-x^2)}{(1-\epsilon)^{1.5}} \quad (15)$$

with $x = \operatorname{erfc}^{-1}(2P/H)$ and $\epsilon = \sqrt{P/H}$. The complex expression of Eq. (15) was correlated by the following simple expression:

$$\frac{oh_c}{k_s} = 1.25 m \left(\frac{P}{H}\right)^{0.95} \quad (16)$$

which agrees with the exact expression to within $\pm 1.5\%$ for $2 < Y/\sigma < 4.75$.

Alternate Development of Contact Conductance

Here we assume N microcontact spots all having the same mean radius a and associated circular flux tube of mean radius b . The total contact resistance is as above

$$R_c = \frac{\psi_c}{2Nk_s a} \quad (17)$$

and the contact conductance is

$$h_c = 2nak_s/\psi_c \quad (18)$$

where n is the contact spot density.

The product of Eqs. (10) and (11) yields

$$na = \frac{1}{4\sqrt{2\pi}} \frac{m}{\sigma} \exp(-x^2) \quad (19)$$

Substitution of Eq. (19) into Eq. (18) gives Eq. (15). To simplify further calculations, two additional correlations for Y/σ and a will be derived.

From Eq. (14) we obtain

$$\sqrt{2}x = Y/\sigma = 1.184[-\ln(3.132P/H)]^{0.547} \quad (20)$$

Multiplying Eq. (11) through by x gives

$$\frac{m}{\sigma} ax = \sqrt{\frac{8}{\pi}} x \exp(x^2) \operatorname{erfc}(x) \quad (21)$$

In the range of interest $1.41 \leq x \leq 3.16$, we can write

$$x \exp(x^2) \operatorname{erfc}(x) \approx 0.52 \quad (22)$$

Substitution of Eqs. (20) and (22) into Eq. (21) yields

$$\frac{ma}{\sigma} = 0.99[-\ln(3.132P/H)]^{-0.547} \quad (23)$$

Knowing the surface characteristics m and σ as well as the relative contact pressure P/H one can compute the mean contact spot radius by means of Eq. (23).

Gap Conductance Correlation

Heat transfer across the gap is very difficult to analyse because of the complexity of the geometry of the gap which determines whether the local heat transfer can be modelled as continuum, slip or rarefied. To overcome these difficulties it is necessary to model the heat transfer from an overall point of view. To this end it will be assumed that the gap heat transfer can be modelled as heat transfer between two isothermal parallel plates which are separated by the distance Y_e which is the effective gap thickness. The effective gap thickness is some fraction of the distance between the mean planes Y .

The simplest model assumes $Y_e = Y$ for greases and liquids which completely wet the two surfaces, and for gases we take

$$Y_e = Y + \alpha \delta \Lambda \quad (24)$$

In Eq. (24) α is the accommodation coefficient defined as

$$\alpha = \frac{2-\alpha_1}{\alpha_1} + \frac{2-\alpha_2}{\alpha_2} \quad (25)$$

where α_1 and α_2 are the accommodation coefficients. These coefficients are complex parameters which depend upon the microgeometry; the gas and solid molecular weights; and surface contaminants such as oxides, films, etc. They are usually determined empirically; typical values for a range of gases are reported by Shlykov.

The fluid parameter β is determined by

$$\beta = \left(\frac{2Y}{Y+1}\right) \frac{1}{Pr} \quad (26)$$

where Y is the specific heat ratio and Pr is the Prandtl number.

The molecular mean free path Λ is dependent upon the gap mean temperature T and the gap pressure P_g ,

$$\Lambda = \Lambda_0 (T/T_0) (P_{g0}/P_g) \quad (27)$$

In Eq. (27) the subscript refers to some reference level.

For the effective gap heat transfer area, we have

$$A_g = A_a (1-\epsilon^2) = A_a \quad (28)$$

because $\epsilon \leq 0.3$; therefore, for the gap conductance, we have

$$h_g = \frac{k_{g0}}{Y + \alpha \beta \Lambda} \quad (29)$$

To nondimensionalize Eq. (29) multiply by (σ/k_s) to obtain the gap conductance correlation

$$\frac{\sigma h_g}{k_s} = \frac{(k_{go}/k_s)}{(Y/\sigma) + \alpha \beta \Lambda_o (T/T_o) (P_{go}/P_g)} \quad (30)$$

or for convenience we write

$$\frac{\sigma h_g}{k_s} = \frac{K}{(Y/\sigma) + M} \quad (31)$$

The relative gap thickness (Y/σ) is determined by means of Eq. (20).

For most practical contact problems the various parameters appearing in Eq. (30) are limited to the ranges shown in Table 1.

Table 1 Typical Ranges of the Parameters

10^{-5}	$< P/H$	$< 10^{-2}$
4.26	$> Y/\sigma$	> 2.34
0.2 μ m	$< \sigma$	$< 4 \mu$ m
0.03	$< m$	< 0.3
2	$< \alpha$	< 10
1	$< \beta$	< 2
0.04 μ m	$< \Lambda_o$	$< 0.19 \mu$ m
0.01	$< \Lambda_o/\sigma$	< 1.0
10^{-4}	$< k_{go}/k_s$	$< 2 \times 10^{-2}$

Joint Conductance Correlation

The contact and gap heat transfer rates are approximately independent for the practical contact problems of interest here. Therefore, the total or joint conductance h_j is equal to the sum of the contact and gap conductances,

$$h_j = h_c + h_g \quad (32)$$

Multiplying by (σ/k_s) gives

$$\frac{\sigma h_j}{k_s} = \frac{\sigma h_c}{k_s} + \frac{\sigma h_g}{k_s} \quad (33)$$

or for convenience as

$$C_j = C_c + C_g \quad (34)$$

Comparison of Theoretical and

Experimental Results

The joint conductance correlation developed in this paper will be compared with the experimental results reported in references 22 and 23. The pertinent geometric, physical and thermal parameters are given in Tables 2 and 3.

Table 2 Geometric, Physical, Thermal Parameters of Reference 22

Solids: Stainless Steel 416 Pair

$k_1 = k_2 = 25.26$	W/mK
$k_s = 25.26$	W/mK
$H_1 = H_2 = 2.59 \times 10^9$	Pa
$H = 2.59 \times 10^9$	Pa
$\sigma_1 = 3.81 \mu$ m	$\sigma_2 = 1.57 \mu$ m
$\sigma = 4.11 \mu$ m	
$m_1 = 0.092$	$m_2 = 0.092$
$m = 0.130$	

Fluid: Air at 377 K and one atmosphere

$k_{go} = 0.0298$	W/mK	$\therefore K = 1.18 \times 10^{-3}$
Assume $\alpha_1 = \alpha_2 = 0.9$	$\therefore \alpha = 2.24$	
$\beta = 1.64$		
$\Lambda_o = 6.40 \times 10^{-8}$	m	$\therefore \frac{\Lambda_o}{\sigma} = 1.50 \times 10^{-2}$
$\frac{T}{T_o} = 1.31,$	$\frac{P_{go}}{P_g} = 1.0$	
$M = \alpha \beta (\Lambda_o/\sigma) (T/T_o) (P_{go}/P_g) = 0.081$		

Table 3 Geometric, Physical, Thermal Parameters of Reference 23

Solids: Molybdenum Copper

k (W/mK)	140	380
H (10^{-8} Pa)	18	5.0
k_s (W/mK)		204.6
H (10^{-8} Pa)		5.0
P		6.90×10^4 Pa
P/H		1.38×10^{-4}
$\sigma_1 = \sigma_2 = 0.625 \mu$ m	$\therefore \sigma = 0.884 \mu$ m	
$m_1 = m_2 = 0.07$ (assumed)	$\therefore m = 0.10$	

Fluid: Air at 288 K and one atmosphere

$k_{go} = 0.0337$	W/mK	$\therefore K = 1.65 \times 10^{-4}$
$\alpha = 2.33$		
$\beta = 1.64$		
$\Lambda_o = 6.40 \times 10^{-8}$	m	
$\frac{\Lambda_o}{\sigma} = 7.24 \times 10^{-2}$		
$\frac{T}{T_o} = 1.00,$	$\frac{P_{go}}{P_g} = 1$	
$M = \alpha \beta (\Lambda_o/\sigma) (T/T_o) (P_{go}/P_g) = 0.277$		

Using Eqs. (16) and (30) with the data given in Table 2, we can develop the following joint conductance correlation for the contact described in reference 22:

$$C_j = 0.163 \left(\frac{P}{H}\right)^{0.95} \frac{1.18 \times 10^{-3}}{0.081 + 1.184 [-\ln(3.132 \frac{P}{H})]^{0.547}} \quad (35)$$

The contact, gap and joint conductances predicted by the theory and the measured joint conductances are presented in Table 4. It can be seen that there is good agreement between the theory and the measured values at three of the five relative contact pressures. The predicted values of C_j are approximately 35% below the measured values at the lowest load and the intermediate load. The author believes that the measured value of $C_j = 17.66 \times 10^{-4}$ is questionable because it is not consistent with the other measured values. It is difficult at this time to say anything about the discrepancy between the theory and the test result corresponding to the lowest value of P/H .

Table 4 Comparison between Theory and Experiment (Ref 22)

$10^4 P/H$	8.92	21.6	40.5	108	216
$10^4 C_c$	2.07	4.79	8.70	22.1	42.7
$10^4 C_g$	3.71	4.05	4.35	4.98	5.63
$10^4 C_j$ (Theory)	5.78	8.84	13.05	27.08	48.33
$10^4 C_j$ (Exp.)	7.72	9.25	17.66	25.43	43.46
% Dif- ference	-33.6	-4.64	-35.3	+6.09	+10.1

By means of Eqs. (16) and (30) and the data given in Table 3, one can determine the contact, gap and joint conductances: $h_c = 6.23 \times 10^3 \text{ W/m}^2\text{K}$, $h_g = 9.75 \times 10^3 \text{ W/m}^2\text{K}$ and $h_j = 15.98 \times 10^3 \text{ W/m}^2\text{K}$. The measured value reported in reference 23 is $h_j = 17.22 \times 10^3 \text{ W/m}^2\text{K}$. It is seen that the agreement is quite good.

In reference 23, a test result with silicon grease is also presented. The experimentally determined joint conductance was found to be: $h_j = 71.76 \times 10^3 \text{ W/m}^2\text{K}$. The present model predicts the gap conductance to be

$$h_g = \frac{k_g}{Y} = \frac{k_g}{\left(\frac{Y}{\sigma}\right)} \quad (36)$$

With $k_g = 0.20 \text{ W/mK}$ for silicon grease (23) Eq. (36) predicts $h_g = 62.36 \times 10^3 \text{ W/m}^2\text{K}$. Adding this value to $h_c = 6.23 \times 10^3 \text{ W/m}^2\text{K}$ yields $h_j = 68.59 \times 10^3 \text{ W/m}^2\text{K}$. The predicted and the measured values are in very good agreement.

Conclusions and Recommendations

The reasonably good agreement between the theoretical and measured values of the joint conductance is most encouraging. However, much more empirical data is required before one can conclude that the contact, gap and joint conductance correlations presented in this paper are valid for all contact conditions. It is recommended that an experimental program should be undertaken to obtain accurate test results for a range of the important contact parameters: P/H , σ/m , K and M .

Acknowledgements

The financial support of the Canadian National Science Engineering Research Council is greatly appreciated. The author also acknowledges the help of Messrs. L. Tessier, K. A. Martin and A. H. Hegazy.

References

1. Graff, W. J., "Thermal Conductance across Metal Joints", Machine Design, Vol. 32, 1960, pp. 166-172.
2. Minges, M. L., "Thermal Contact Resistance", USAF Report AFML-TR-65-375, 1966.
3. Thomas, T. R. and Probert, S. D., "Thermal Contact of Solids", Chemical and Process Engineering, Vol. 47, 1966, pp. 51-60.
4. Fry, E. M., "Contact Thermal Conductance", Bell Telephone Laboratories, Report No. 101, 1966.
5. Atkins, H., "Bibliography on Thermal Metallic Contact Conductance", NASA - George C. Marshall Space Flight Center, Technical Report X-53227, 1965.
6. Wong, H. Y., "A Survey of the Thermal Conductance of Metallic Contacts", Aeronautical Research Council Report C. P. 973, HMSO, London, 1968.
7. Hsieh, C. K. and Davis, F. E., "Bibliography on Thermal Contact Conductance", USAF Report AFML-TR-69-24, 1969.
8. Moore, C. J., Atkins, H. and Blum, H. A., "Subject Classification Bibliography for Thermal Contact Resistance Studies", ASME Paper 68-WA/HT-18, New York, 1968.
9. Veziroglu, T. N., "Correlation of Thermal Contact Conductance Experimental Results", University of Miami Mechanical Engineering Department Report, NASA Grant NGR 10-007-101-Sub 11, 1967.
10. Tien, C. L., "A Correlation for Thermal Contact Conductance of Nominally Flat Surfaces in a Vacuum", Proceedings 7th Thermal Conductivity Conference, U. S. Bureau of Standards, 1968, pp. 755-759.

- 11 Holm, R., "Thermal Conduction through Nominally Flat Metallic Contacts in Vacuum Environment", Stackpole Carbon Co. Report, 1965.
- 12 Fried, E., "Study of Interface Thermal Contact Conductance", General Electric Co. Report 65SD4395, 1965.
- 13 Bloom, M. F., "Thermal Contact Conductance in a Vacuum Environment", Douglas Aircraft Co. Report SM47700, 1964.
- 14 Cooper, M. G., Mikić, B. B., and Yovanovich, M. M., "Thermal Contact Conductance", International Journal of Heat and Mass Transfer, Vol. 12, 1969, pp. 279-300.
- 15 Clausing, A. M. and Chao, B. T., "Thermal Contact Resistance in a Vacuum Environment", Journal of Heat Transfer, Trans. ASME, Series C, Vol. 87, No. 2, 1965, pp. 243-251.
- 16 Shlykov, Yu. P. and Ganin, Ye. A., "Thermal Resistance of Metallic Contacts", International Journal of Heat and Mass Transfer, Vol. 7, 1964, pp. 921-929.
- 17 Shlykov, Yu. L., "Calculating Thermal Contact Resistance of Machined Metal Surfaces", Teploenergetika, Vol. 12, 1965, pp. 102-108.
- 18 Yovanovich, M. M. and Fenech, H., "Thermal Contact Conductance of Nominally Flat Rough Surfaces in a Vacuum Environment", AIAA Progress in Astronautics and Aeronautics, Vol. 18, 1965 pp. 773-794.
- 19 Mikić, B. B., "Analytical Studies of Contact of Nominally Flat Surfaces; Effect of Previous Loading", Journal of Lubrication Technology, 1971, pp. 451-459.
- 20 Mikić, B. B., "Thermal Contact Conductance; Theoretical Considerations", International Journal of Heat and Mass Transfer, Vol. 17, 1973, pp. 205-214.
- 21 Montes, A., Veziroglu, T. N., Samudrala, R., Sheffield, J. W., and Williams, A., "Effects of Interface Gases on Contact Conductance", AIAA-81-0214, 1981.
- 22 Henry, J. J., "Thermal Contact Resistance", Ph.D. Thesis, MIT, 1964.
- 23 Seely, J. H., and Chu, R. C., Heat Transfer in Microelectronic Equipment, A Practical Guide, Marcel Dekker, Inc., New York, 1972.