

Week 7: Lecture 2


Air Standard Cycle

Assumptions

- air is an ideal gas with constant c_p and c_v
- no intake or exhaust processes
- the cycle is completed by heat transfer to the surroundings
- the internal combustion process is replaced by a heat transfer process from a TER
- all processes are reversible
- heat addition occurs instantaneously while the piston is at TDC

Otto Cycle

- consists of four internally reversible processes
- heat is transferred to the working fluid at constant volume




$$\eta_{Otto} = 1 - r^{1-k} \quad \text{where :} \quad r = \frac{V_1}{V_2} = \frac{V_4}{V_3} \quad (\text{compression ratio})$$

Otto cycle limitations on compression ratio

- increased tendency for the fuel to detonate as the compression ratio increases
- the pressure wave gives rise to engine knock
- can be reduced by adding tetraethyl lead to the fuel
- not good for the environment

Week 7: Lecture 2



The Diesel Cycle

- heat is transferred to the working fluid at constant pressure

$$\eta_{Diesel} = 1 - \frac{1}{r^{k-1}} \left(\frac{1}{k} \right) \left(\frac{r_v^k - 1}{r_v - 1} \right) \quad \text{where :} \quad r_v = \frac{V_3}{V_2} = \text{ (volume ratio)}$$

Comparison of the Otto and the Diesel Cycle

- $\eta_{Otto} > \eta_{Diesel}$ for the same compression ratio
- but a diesel engine can tolerate a higher ratio since only air is compressed in a diesel cycle and spark knock is not an issue
- direct comparisons are difficult

