Week 5: Lecture 1

Refrigeration Cycle

A refrigeration system removes thermal energy from a low-temperature region and transfers heat to a high-temperature region.

The Carnot cycle can serve as the initial model of the ideal refrigeration cycle.

- operates as a reversed heat cycle engine
- transfer a quantity of heat, Q_L from a cold source at temperature, T_L





where:

$$
\begin{aligned}
Q_L &= T_L(s_3 - s_2) \\
Q_H &= T_H(s_4 - s_1) \\
W_{in} &= Q_{net} \\
&= (T_H - T_L)(s_3 - s_2)
\end{aligned}
$$

Coefficient of Performance

$$COP = \frac{benefit}{cost}$$

$$
\begin{aligned}
COP_{refrig} &= \frac{Q_L}{W_{in}} = \frac{1}{\dfrac{T_H}{T_L} - 1} = \frac{T_L}{T_H - T_L} \\
COP_{heat\ pump} &= \frac{Q_H}{W_{in}} = \frac{1}{1 - \dfrac{T_L}{T_H}} = \frac{T_H}{T_H - T_L}
\end{aligned}
$$

Week 5: Lecture 1

Vapour Compression Refrigeration Cycle

Assumptions for Ideal VCRC

- irreversibilities within the evaporator, condenser and compressor are ignored
- no frictional pressure drops
- refrigerant flows at constant pressure through the two heat exchangers
- stray heat losses to the surroundings are ignored
- compression process is isentropic







1-2s:	isentropic compression of the refrigerant
2s-3:	heat transfer from the refrigerant as it flows at constant pressure through the condenser
3-4	throttling process from state 3 to a two phase liquid-vapour mixture at state 4
4-1	heat transfer to the refrigerant as it flows at constant pressure through the evaporator